



Pebble

Powerful, easy-to-use and cost-effective, the **Pebble** color printer personalizes and encodes all your plastic cards: identification, security, loyalty and leisure badges.

The **Pebble** prints your high resolution texts, logos, pictures, signatures and barcodes in a few seconds. It also offers optional magnetic encoding, smart card encoding and contactless card personalization.

Powerful and reliable, the **Pebble** is designed to answer all needs, from small card series to printing in volume.

The **Pebble** is a turnkey solution. Delivered as standard with user-friendly software for badge personalization and drivers for Windows™ or Mac OS X, it is as easy-to-use as a classical office printer.

The **Pebble** comes in three colors: Lagoon, Ruby and Glacier. Its Hi-Tech design, compactness and ergonomics allow it to integrate any reception or office desk.

With an excellent quality/price ratio, the **Pebble** is **the referent single-sided color printer on the market**.



Print mode

- Color dye sublimation and monochrome thermal transfer
- Edge-to-edge printing standard

Printer specifications

- Integrated ribbon saver for monochrome printing

Print speed

- 150 cards/hour in full color (YMCKO)
- Up to 1000 cards/hour in monochrome¹

Resolution

- 300 dpi (11.8 dots/mm)

Printer colors

- Glacier, Lagoon or Ruby

Software supplied

- eMedia Card Designer for designing and editing badges
- Compatible with Windows™ NT 4.0, 2000 and Xp

Drivers

- For Windows™ NT 4.0, 2000 and Xp
- For Mac™ OS X v10.2 and v10.3

Warranty

- Printer: 2 years
- Print head: 2 years, unlimited number of prints²

Ribbon types

- Monochrome ribbon: 1000 cards/roll (black, blue, red, green, white, gold, silver and scratch off)
- BlackWAX monochrome ribbon (for ABS and special varnished plastic cards): 1000 cards/roll
- 2 panel black monochrome ribbon (KO): 500 cards/roll
- 5 panel color ribbon (YMCKO): 200 cards/roll
- Half-panel color ribbon (YMCKO): 400 cards/roll
- Hologram ribbon: 350 cards/roll

Card loading modes

- Automatic with feeder or hand-feed

Options

- HICO/LOCO magnetic stripe encoder (3-tracks), ISO 7811, field upgradeable
- Serial port (available upon study)
- Hand-feed cartridge
- 100-card additional feeder
- Softcase for demonstration
- Cleaning kit

Other printer models

- **Pebble Mag** - Printer with HICO/LOCO magnetic stripe encoder - ISO 7811
- **Pebble Smart** - Printer with smart card contact station - ISO 7816-2
- **Pebble Contactless** - Printer with contactless smart card coupler

- 1 - UNW specific conditions
- 2 - Choice goes through the list of basic ribbons



Card types	PVC, Composite PVC, PET, ABS and special varnished plastic cards
Card format	ISO CR-80 - ISO 7810 (85,65 mm x 85,60 mm - 3.375" x 2.125")
Card thickness	From 0,25 mm (10 mil) to 1 mm (40 mil)
Card feeder capacity	300 cards (0,25 mm - 10 mil) - 100 cards (0,76 mm - 30 mil)
Card output hopper capacity	150 cards (0,25 mm - 10 mil) - 50 cards (0,76 mm - 30 mil)
Resident barcodes	Code 39, Code 2/5 interleaved
Resident fonts	Arial normal 100, Arial bold 100
Printer size	Height: 192 mm (7.56") - Length: 394 mm (15.51") - Width: 225 mm (8.85")
Printer weight	5,9 Kg (13 lbs)
Connections	USB and Centronics parallel ports (cables supplied)
Electrical	110-230 Volts CA, 60-50 Hertz
Environmental	<ul style="list-style-type: none"> • Min / max operating temperature: 15° / 30° C (59° / 66° F) • Humidity: 20% to 65% non-condensing • Min / max storage temperature: -5° / +35° C (23° / 158° F) • Storage humidity: 20% to 70% non-condensing • Operating ventilation: free air



Headquarters:
Willow Print Technology Ltd

Unit 21, Phoebe Lane Mills, Siddal, Halifax, West Yorkshire, HX3 9EX. UK
Tel: +44 (0)1422 382400 Fax: +44 (0)1422 382401 Email: info@willowtechnology.com