

DROP-IN



3 inch Impact Dot POS Printer SRP-275II



BIXOLON SRP-275II is more powerful and enhanced performance impact dot POS printer to address customers' needs in restaurant, hospitality and retail industries. The fastest speed in its class(5.1 lps) allows kitchen orders to print faster than ever with two color, black and red printing to highlight special offers and print logos. Compact size with embedded power supply maximizes the efficiency of working environment. Eco-friendly design of the lowest standby power and various international standards provide reliability of the SRP-275II to the users.

BR-SRP-275II-EN-MAR14

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

BIXOLON®

www.bixolon.com



BIXOLON Co., Ltd.

7~8F, (Sampyeong-dong), 20, Pangyoeyeok-ro241beon-gil,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

PRINT CHARACTERISTICS

Print Method : 9 Pin / Serial Dot Matrix

Print Speed : 5.1 lps

Print Resolution : 80 dpi (horizontal) / 144 dpi (vertical)

Print Width : Up to 63.5 mm

Sensor : Paper End, Paper Near End, Wall Mounting Paper Near End,
Rear Cover Open, Black Mark

MEDIA CHARACTERISTICS

Media Type : Receipt

Media Width : 76.5 mm

Media Roll Diameter : Up to 83 mm

Media Roll Diameter : 0.06 ~ 0.085 mm

Supply Method : Easy Paper Loading

PHYSICAL CHARACTERISTICS

Dimensions (W x L x H) : 160 x 239 x 157 mm
(6.29 x 9.40 x 6.18 inch)

Weight : A: 2.4 kg (5.29 lbs.) / C: 2.5 kg (5.51 lbs.)

Power : EnergyStar Certified,
External Power Adaptor 100-240V AV, 50/60Hz

Drawer Port : 2 ports (via y-type adaptor)

PERFORMANCE CHARACTERISTICS

Memory : 64 Mbit SDRAM, 16 Mbit FlashROM

NV Image Memory : 256 Kbytes

Receive Buffer : 64 Kbytes

User Define Buffer : 64 Kbytes

Interface : USB V2.0 HS, Serial, Parallel, Ethernet

ENVIRONMENT CHARACTERISTICS

Temperature : Operating: 0 ~ 40°C (32 ~ 104°F)
Storage: -20 ~ 60°C (-4 ~ 140°F)

Humidity : Operating: 10 ~ 80% RH
Storage: 10 ~ 90% RH

RELIABILITY

Printer Unit (MCBF) : 18 Million Lines

TPH : 300 Million Dots/Wire

Auto Cutter : 1.5 Million Cuts

SOFTWARE

Emulation : BXL / POS

Driver : Windows Driver, OPOS Driver, JPOS Driver, Linux CUPS Driver,
Mac Driver, Virtual COM USB/Ethernet Driver, Utility Program

SDK : iOS SDK, Android SDK

FONTS / GRAPHICS / SYMBOLOGIES

Character Size : Font A: 9 x 9 Font B: 7 x 9 / KOR: 17 x 9 CHN: 16 x 16

Characters Per Line : Font A: 35 Font B: 40 / KOR: 20 CHN: 22

Character Sets : Alphanumeric: 95

Extended Graphics: 128 x 27 page

International: 48

Graphics : Supporting user-defined fonts, graphics, formats, and logos

ACCESSORIES

Optional : Wall Mount (RWM-350)

Splash Proof Cover (RSC-275)

B-melodist (RMB-100)

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de